

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
18 September 2003 (18.09.2003)

PCT

(10) International Publication Number
WO 03/075954 A1

- (51) International Patent Classification⁷: **A61K 39/04**, 39/39, A61P 31/06, 35/00
- (21) International Application Number: PCT/IB03/00787
- (22) International Filing Date: 3 March 2003 (03.03.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2002/1965 8 March 2002 (08.03.2002) ZA
- (71) Applicant (for all designated States except US): **HYDROFUEL (PROPRIETARY) LIMITED [ZA/ZA]**; Taxi Trucks House, Gerry Ferry Avenue, Epping Industria, 7460 Eppindust (ZA).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **MAWDSLEY, Michael, John [ZA/ZA]**; 4 Hillbrow Road, 3610 Kloof (ZA).
- (74) Agent: **BAGNALL, Russell, Anthony**; Adams & Adams, Adams & Adams Place, 1140 Prospect Street, Hatfield, PO Box 1014, 0001 Pretoria (ZA).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FUEL ADDITIVE

(57) Abstract: An emulsifying composition which includes an ethoxylated alkylphenol, a fatty acid amide, naphtha and oleic acid. The composition is used for emulsifying fuel and water mixtures in internal combustion engines, open flame burners (boilers) or the like. Preferably the composition includes one part polyoxyethylene -nonylphenol, two parts coconut diethanolamide, two parts heavy naphtha and one part oleic acid, by volume. The invention also extends to a hydrocarbon fuel including a composition in accordance with the invention and to a method of forming a hydrocarbon fuel and water emulsion including the composition.

WO 03/075954 A1

FUEL ADDITIVE

THIS INVENTION relates to fuels. In particular, the invention relates to an emulsifying composition, to a hydrocarbon fuel, and to a method of forming a hydrocarbon fuel and water emulsion.

5 According to the invention, there is provided an emulsifying composition which includes
 an ethoxylated alkylphenol;
 a fatty acid amide;
 naphtha; and
10 oleic acid.

 It is to be understood that the invention finds substantial utility as a composition for emulsifying fuel and water mixtures used in internal combustion engines, open flame burners (boilers), or the like. However, the invention is not limited to this application and may also be
15 used in other applications such as a cleaning agent, for example, lifting oil deposits from surfaces such as tarred roads, concrete, masonry, or the like.

The ethoxylated alkylphenol is a non-ionic surfactant of general formula $R(\text{OCH}_2\text{CH}_2)_n\text{OH}$ in which R is alkylphenol and n represents the number of ethoxy groups.

5 The ethoxylated alkylphenol may be polyoxyethylene (POE)-nonylphenol, for example, a product available from ICI under the tradename SYNPERONIC NP. In a preferred embodiment of the invention, POE-(5) or POE(6)-nonylphenol may be used, for example, SYNPERONIC NP5 or SYNPERONIC NP6.

10 The fatty acid amide may be a fatty acid dialkanolamide. In a preferred embodiment of the invention, the fatty acid amide may be coconut diethanolamide, for example, a product available from Albright & Wilson under the tradename EMPILAN 2502.

The naphtha may be heavy naphtha.

15 In a preferred embodiment of the invention, the composition may include polyoxyethylene-nonylphenol, coconut diethanolamide and heavy naphtha. Preferably, the composition may contain one part polyoxyethylene -nonylphenol, two parts coconut diethanolamide, two parts heavy naphtha and one part oleic acid, by volume.

20 The invention also extends to a hydrocarbon fuel including a composition in accordance with the invention.

The hydrocarbon fuel may be an alcohol based fuel, gasoline (petrol), diesel fuel e.g. sweet diesel, or mixtures thereof.

The hydrocarbon fuel may include up to about 40% water, by volume. Preferably, the hydrocarbon fuel may contain up to about 25% water.

5 The hydrocarbon fuel may include between about 1.5% and 2%, by volume, of the composition.

According to another aspect of the invention, there is provided a method of forming a hydrocarbon fuel and water emulsion which includes adding an ethoxylated alkylphenol, a fatty acid amide, naphtha and oleic acid to a hydrocarbon fuel to form a mixture and
10 adding water to said mixture.

Preferably, the method includes forming an additive composition containing the ethoxylated alkylphenol, the fatty acid amide, the oleic acid and the naphtha and adding said additive composition to the hydrocarbon fuel.

15 Preferably, a composition including one part polyoxyethylene-nonylphenol, two parts coconut diethanolamide, one part oleic acid and two parts heavy naphtha, by volume, is added to the hydrocarbon fuel to form the mixture.

Advantageously, the constituents of the additive are mixed
20 in the order polyoxyethylene-nonylphenol, coconut diethanolamide, oleic acid and naphtha to form the composition.

The invention will now be described, with reference to the following non-limiting examples and tests.

EXAMPLE 1

A batch additive composition in accordance with the invention containing one part polyoxyethylene -nonylphenol (SYNPERONIC NP5 or 6), two parts coconut diethanolamide (EMPILAN 2502), one part oleic acid and two parts heavy naphtha was prepared. These components were mixed in the order stated above. 1.8 litres of the batch composition was added to 71.79 litres (15.792 imperial gallons) of a base hydrocarbon fuel. The base fuel used was a 70 - 30 blend of No. 5 fuel oil containing 70% Bunker C fuel and 30% diesel fuel, by volume. The mixture of the composition and base fuel was agitated using compressed air and was left for approximately 2 - 5 minutes to allow dispersion of the composition and the fuel oil. Thereafter, 23.93 litres (5.264 gallons) of water was added to the mixture. The resultant mixture was agitated using compressed air for approximately 2 - 5 minutes to allow the fuel/water emulsion to form. If necessary, a second agitation may be carried out after 20 minutes. As will be appreciated from the above volumetric amounts the resultant mixture contains about 25% water and about 1.86% of the composition, by volume, in the final blend.

For the purpose of the tests described below a 74.6 KW (100 horsepower) Scotch Marine Boiler with a full modulation industrial combustion Hev-e-Oil burner was used. The boiler was modified to accept fuel from two sources, namely, a main tank containing the No. 5

blend fuel oil described above (without the additive) and an auxiliary tank containing the fuel prepared in accordance with Example 1. Return lines of the boiler were re-piped to re-circulate through the main fuel oil pump and the burner bypass valve respectively. This enabled the fuel supplied to the boiler to be changed, between the two sources as required, without a return oil consideration. A series of tests were conducted using the boiler and the compositions described above, as is set out in more detail below.

TEST NO. 1

- 10 The boiler was run initially on the No. 5 fuel oil provided in the main tank until the boiler pressure reached about 344 KPa (50 pounds per square inch (psi)). Once this pressure was reached the operation of the boiler was switched over to the fuel prepared in accordance with Example 1 for an initial inspection of the flame. A smooth changeover was observed.
- 15 The flame was well defined and appeared tighter and longer than the No. 5 fuel oil flame. The boiler was operating in automatic full modulating mode. The boiler was noticeably quieter in operation when the changeover occurred. A steam pressure increase to about 361.7 KPa (52.5 psi) was also observed.

TEST NO. 2

The boiler was fired up using the fuel prepared in accordance with Example 1 and brought up to the operating temperature of approximately 361.7 KPa (52.5 psi). The boiler was set in manual mode at near high
5 fire position to fix the position of all fuel air ratio linkages in order to obtain a comparison of the No. 5 fuel oil and the fuel in accordance with Example 1, under the same conditions. The boiler was not set for optimum efficiency during this run. Combustion tests were conducted on both fuels using an Enerac 2000 combustion analyzer which measured
10 carbon dioxide, carbon monoxide, combustible gas, excess air and oxygen emissions. These results are set in Table 1 below. The test results show a reduction in carbon dioxide, carbon monoxide and combustible gas emissions using the fuel in accordance with the invention, despite an increase in excess air and oxygen.

15

TEST NO. 3

A steam flow capacity test was conducted. In order to do this a flow meter was installed between the feed water supply pump and the boiler. The boiler was run on the fuel in accordance with Example 1 and was brought up to an operating pressure of approximately 379 KPa (55 psi).
20 The steam capacity was randomly measured at about 832.6 kg per hour (1834 pounds per hour). This was calculated by measuring the amount of water entering the boiler using the flow meter over a predetermined period and by relying on the accepted relationship between mass and gallons of water evaporated in the boiler industry i.e. that the

mass of steam in pounds per hour divided by 500 is equal to the gallons of water per minute evaporated.

TEST NO. 4

5 The steam flow capacity of the fuel in accordance with Example 1 was compared with that of the No. 5 blend oil. A fixed fire held in place by placing the boiler in manual operating mode was achieved. The results of this test showed that the fuel in accordance with Example 1 generated steam at a rate of about 1114.7 kg/h (2235 pounds per hour) based on evaporating about 345.4 litres (76 gallons) of water in 17 minutes and
10 the No. 5 fuel oil generated steam at a rate of about 983.8 kg per hour (2167 pounds per hour) based on evaporating about 295.4 litres (65 gallons) of water in 15 minutes. The average stack temperatures were measured at approximately 265.6°C (510°F) for the fuel in accordance with Example 1 and approximately 246.1°C (475°F) for the No. 5 fuel
15 oil.

TEST NO. 5

A stability test to observe the emulsifying characteristics of the fuel in accordance with the invention was conducted. A batch of fuel prepared in accordance with Example 1 was left for approximately 6 days and then
20 the boiler was fired up. A clean burn was observed without any indication of fuel separation. An additional 22.7 litres (5 gallons) of fuel in accordance with Example 1 from a separate batch was added to the auxiliary tank during this run. There was no visual indication of separation while the additional fuel was being added and there was no

difference in the flame in the burner. The boiler was run until the entire fuel batch was depleted.

TEST NO. 6

A further emission test was conducted by running the boiler near optimum efficiency. The test was started on a No. 5 fuel oil batch and then the boiler was changed over to a fuel prepared in accordance with Example 1 without any adjustments in the fuel/air ratio. The emissions of oxides of nitrogen and sulfur dioxide were measured using the Enerac 2000 analyzer and the combustion efficiencies were calculated. The results are set out in Table 1 below.

TABLE 1 - A comparison between the fuel in accordance with the invention and the No. 5 fuel oil.

	FUEL IN ACCORDANCE WITH EXAMPLE 1	NO. 5 FUEL OIL
Combustion Efficiency	74.9%	83.5%
Ambient Temperature	32.2°C (90°F)	28.9°C (84°F)
Stack Temperature	260.6°C (501°F)	255.6°C (492°F)
Oxygen	9.3%	5.7%
Carbon Monoxide	16 ppm	77 ppm
Carbon Dioxide	9.0%	12.2%
Combustible Gases	0.39%	0.00%
Excess Air	76.0%	34.0%
Oxides of Nitrogen	95 ppm	120 ppm
Sulphur Dioxide	708 ppm	880 ppm

TEST NO. 7

A comparative test was conducted to determine the amount of fuel consumed to produce a given quantity of steam for both fuels. Each test was started immediately after feed water supply pump was shut off and the fuel valve was simultaneously opened. The starting time was noted and the water supply reading was noted. Each test was conducted using 23.9 litres (5.264 gallons) of the fuel. Each sample was weighed beforehand. Each test was stopped by shutting off the fuel valve and noting the time at a later feed water supply shut off. The feed water pump was controlled automatically through a MacDonnel Miller No. 157 assembly that engaged the pump at a fixed low water point and disengaged the pump at a fixed high water point. The test results are set out in Table 2 below.

TABLE 2 - Comparative fuel consumption tests.

	PARAMETERS	FUEL IN ACCORDANCE WITH EXAMPLE 1	NO. 5 FUEL OIL
	Weight of Fuel per Gallon	3.73 kg (8.21 lbs)	3.69 kg (8.12 lbs)
5	Fuel used per Minute	1.56 kg (3.44 lbs)	1.58 kg (3.47lbs)
	Volume of Fuel used per minute	1.95 litres (0.43 gal)	1.91 litres (0.42 gal)
	Duration of Test	13 min	10.25 min
10	Volume of Water Supplied	209.1 litres (46 gal)	150.1 litres (33 gal)
	Steam Generating Rate lbs/hour	803.6 (1770 lbs/hour)	730.94 litres (1610 lbs/hour)
15	Mass of Steam Generated per Minute	13.39 kg (29.50 lbs/hour)	12.19 kg (26.84 lbs)

EXAMPLE 2

A fuel in accordance with the invention was prepared in a similar fashion to Example 1 except that the composition was mixed with diesel fuel instead of the No. 5 blend fuel oil. A series of bench tests on an internal combustion engine - RICARDO P6 Diesel fuel test engine were carried out using the fuel in accordance with the invention. A similar bench test was carried out using a diesel fuel control sample. The results of the control sample test and the test on the fuel in accordance with the invention are set out in Tables 3 and 4.

TABLE 3 - Diesel Fuel Control Test - Ambient temperature 25°C.
Atmospheric pressure 76.70 (Cm.HA).

5

SPEED (RPM)	BALANCE LOAD (kgs)	POWER (KW)	50ML FUEL CONSUMED (SECS)	FUEL FLOW RATE (litres per hour)	SFC (L/KW.H R)	BMBP (KN/M ²)	EXHAUST TEMP (°C)
800	4.54 (10.00 lbs)	1.78				504.34	401.00
1000	4.40 (9.70 lbs)	2.07				489.21	422.00
1200	4.79 (10.55 lbs)	2.70	95.97	1.88	0.70	532.08	452.00
1400	5.27 (11.60 lbs)	3.46				585.03	488.00
1600	5.47 (12.05 lbs)	4.11				607.73	509.00
1800	5.76 (12.70 lbs)	4.87	62.10	2.90	0.68	640.51	512.00
2000	5.99 (13.20 lbs)	5.63				665.73	536.00
2200	6.04 (13.30 lbs)	6.23				670.77	549.00
2400	5.90 (13.00 lbs)	6.65	43.85	4.10	0.62	655.64	566.00

10

TABLE 4 - Test on fuel in accordance with the invention - Ambient temperature 25°C - Atmospheric Pressure 76.70 (CM.HA)

	SPEED (RPM)	BALANCE LOAD (kgs)	POWER (KW)	50ML FUEL CONSUMED (SECS)	FUEL FLOW RATE (litres per hour)	SFC (L/KW.H R)	BMBP (KN/M ²)	EXHAUST TEMP (°C)
5	800	5.65 (12.45 lbs)	2.12				629.90	344.00
	1000	5.79 (12.75 lbs)	2.72				643.03	374.00
	1200	5.81 (12.80 lbs)	3.27	95.65	1.88	0.57	645.55	403.00
	1400	5.95 (13.10 lbs)	3.91				660.68	422.00
	1600	5.92 (13.05 lbs)	4.45				658.16	439.00
10	1800	6.08 (13.40 lbs)	5.16	62.75	2.87	0.56	678.43	461.00
	2000	1.77 (13.90 lbs)	5.92				701.03	504.00
	2200	6.36 (14.00 lbs)	6.56				706.07	532.00
	2400	6.24 (13.75 lbs)	7.03	44.75	4.02	0.57	693.47	547.00

The results indicate similar to slightly less fuel consumption rates for the fuel in accordance with the invention when compared with the control fuel over a range of rpm values but with an increase in power

output. The exhaust temperatures are also shown to be less in Table 4 as compared with Table 3. Unburnt deposits were also at least reduced when the engine was run on the fuel in accordance with the invention.

5 The Applicant believes that it is an advantage of the invention that the composition in accordance with the invention provides a relatively cost effective fuel extender for internal combustion engines, marine boiler applications i.e. open flame burners, or the like. The constituents used in the composition are readily accessible at relatively low cost and are easily cold mixed. The selection of the four
10 constituents enable effective results to be achieved by adding relatively small quantities of the composition to the fuel with significant water additions (Typically 3:1 fuel to water). The Applicant also believes that no significant adjustment in quantities of the composition are required over a range of light to heavy fuels. The Applicant believes that it is a
15 further advantage of the invention that the final blend is a stable emulsion which shows no signs of settling over sustained periods.

The Applicant also believes that it is an advantage of the invention that the composition provides a relatively clean burning and, therefore, environmentally friendly fuel. The oxides of nitrogen and
20 sulphur, carbon monoxide and carbon dioxide contents are reduced as compared to fuels not containing the composition. In addition, oxygen content and excess air evident in the exhaust emissions show substantial increases and there is also a substantial reduction in smoke or unburnt carbon.

The Applicant also believes that the fuel in accordance with the invention improves engine life as a result of the drop in exhaust temperatures.

5 It is a further advantage of the invention that the composition is odourless, non-acidic, non-toxic and, therefore, does not harm the skin if handled. In addition, the flash point of the composition is substantially the same as the fuel with which it is mixed and, therefore, safety aspects in handling and transportation are not compromised by including the composition in a fuel.

10 The Applicant also believes that the composition may be directly substituted for normal hydrocarbon fuel subject to possible minor adjustments to air and fuel flows to optimise performance.

15 Internal combustion engines which have been running on normal diesel fuel experience carbon build-up and other fuel derived deposits. The Applicant believes these may be broken down and exhausted when the engine is run on fuels including the composition in accordance with the invention. Even after prolonged usage, engine components, particularly fuel pump components exhibit no adverse wear or corrosion and older engines appear to run more smoothly.

20 For a given rpm the test in Example 2 showed that the engine running on the fuel in accordance with the invention required comparative to slightly less fuel flow rates to the diesel fuel and, at which flow rate, the power output increased. The exhaust temperature also significantly decreased. It is also believed that the lower rpm for the

same power output and a lower operating temperature contributes to an improvement in engine life.

The Applicant also believes that the problem of oil spill disasters may be alleviated by including the composition in bulk volumes of fuel transported on tankers. The emulsifying properties of the composition would alleviate the problem of oil slick formation in water.

CLAIMS:

1. An emulsifying composition which includes
an ethoxylated alkylphenol;
a fatty acid amide;
5 naphtha; and
oleic acid.
2. A composition as claimed in Claim 1, in which the
ethoxylated alkylphenol is polyoxyethylene (POE)- nonylphenol.
3. A composition as claimed in Claim 1 or Claim 2, in which
10 the fatty acid amide is a fatty acid dialkanolamide.
4. A composition as claimed in Claim 3, in which the fatty acid
dialkanol amide is coconut diethanolamide.
5. A composition as claimed in any one of Claims 1 to 4
inclusive, in which the naphtha is heavy naphtha.
- 15 6. A composition as claimed in Claim 1, in which the
ethoxylated alkylphenol is a polyoxyethylene-nonylphenol, the fatty acid
amide is coconut diethanolamide and the naphtha is heavy naphtha, and
in which the composition contains one part polyoxyethylene -
nonylphenol, two parts coconut diethanolamide, two parts heavy naphtha
20 and one part oleic acid, by volume.

7. A hydrocarbon fuel which includes a composition as claimed in anyone of Claims 1 to 6 inclusive.
8. A hydrocarbon fuel as claimed in Claim 7, which includes up to 40% water, by volume.
- 5 9. A hydrocarbon fuel as claimed in Claim 8, which includes up to 25% water, by volume.
10. A hydrocarbon fuel as claimed in any one of Claims 7 to 9 inclusive, which includes between 1.5% and 2%, by volume, of the emulsifying composition.
- 10 11. A method of forming a hydrocarbon fuel and water emulsion which includes adding an ethoxylated alkylphenol, a fatty acid amide, naphtha and oleic acid to a hydrocarbon fuel to form a mixture and adding water to said mixture.
12. A method as claimed in Claim 11, which includes forming
15 an additive composition containing the ethoxylated alkylphenol, the fatty acid amide, the oleic acid and the naphtha and adding said additive composition to the hydrocarbon fuel.
13. A method as claimed in Claim 12, in which the additive
20 composition includes one part polyoxyethylene-nonylphenol, two parts coconut diethanolamide one part oleic acid, by volume, and two parts heavy naphtha, by volume.

14. A method as claimed in Claim 12 or Claim 13, in which the additive composition is formed by mixing its constituents in the order polyoxyethylene-nonylphenol, coconut diethanolamide, oleic acid and naphtha.
- 5 15. A composition as claimed in Claim 1, substantially as herein described.
16. A hydrocarbon fuel as claimed in Claim 7, substantially as herein described.
17. A method of forming a hydrocarbon fuel and water emulsion
10 as claimed in Claim 11, substantially as herein described.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/IB 03/00787-0

CLASSIFICATION OF SUBJECT MATTER

IPC⁷: C10L 1/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC⁷: C10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

AT, Chemical Abstracts

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO:WPI STN:CAS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4173455 A (FODOR et al.) 6 November 1979 (06.11.79) <i>claims 1-10.</i>	1-17
A	JP 61 114724 A (NIPPON OILS & FATS CO LTD) 2 June 1986 (02.06.86) (abstract). [online] [retrieved on 22.4.2003]. Retrieved from: EPOQUE WPI Database.	1-17
A	SU 1243342 A1 (AZE V S) 15 April 1994 (15.04.94) (abstract). [online] [retrieved on 22.4.2003]. Retrieved from: EPOQUE WPI Database	1-17

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

„A“ document defining the general state of the art which is not
considered to be of particular relevance

„E“ earlier application or patent but published on or after the international
filing date

„L“ document which may throw doubts on priority claim(s) or which is
cited to establish the publication date of another citation or other
special reason (as specified)

„O“ document referring to an oral disclosure, use, exhibition or other
means

„P“ document published prior to the international filing date but later than
the priority date claimed

„T“ later document published after the international filing date or priority
date and not in conflict with the application but cited to understand
the principle or theory underlying the invention

„X“ document of particular relevance; the claimed invention cannot be
considered novel or cannot be considered to involve an inventive step
when the document is taken alone

„Y“ document of particular relevance; the claimed invention cannot be
considered to involve an inventive step when the document is
combined with one or more other such documents, such combination
being obvious to a person skilled in the art

„Z“ document member of the same patent family

Date of the actual completion of the international search

22 April 2003 (22.04.2003)

Date of mailing of the international search report

15 July 2003 (15.07.2003)

Name and mailing address of the ISA/AT

Austrian Patent Office

Dresdner Straße 87, A-1200 Vienna

Facsimile No. 1/53424/535

Authorized officer

BÖHM K.

Telephone No. 1/53424/437

INTERNATIONAL SEARCH REPORT

International application No.
PCT/IB 03/00787-0

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
JP	A2	61114724	02-06-1986	none		
SU	A	1243342		none		
US	A	4173455	06-11-1979	BE	A1	879321
				BR	A	7908847
				CA	A1	1115054
				DK	A	1683/80
				EP	A1	20449
				JP	T2	55500780
				WO	A1	8000710
						01-02-1980
						04-08-1981
						29-12-1981
						21-04-1980
						07-01-1981
						16-10-1980
						17-04-1980